

extensive range
leading brands
design & install

SAFE & SECURE
ONLINE SHOPPING

australia wide authorised catering equipment distributor

Visit Australia's leading Commercial Catering Equipment website for instant quotes on the major catering equipment brands at very competitive prices.

www.mvocateringsolutions.com.au

Showroom locations

MVO Services
3 Toonburra Street
Bundaberg QLD 4670
Ph (07) 4152 7277

MVO Services
5/85 Beach Road
Hervey Bay QLD 4655
Ph (07) 4194 0722

Your requested document is included below



Non Gastronorm Upright Refrigerators and Freezers

Ruby

Benefits

- Available in two or three door models
- Self contained or remote cabinets to suit all refrigeration requirements
- Forced draught cooler in both freezer and refrigerator models
- Colorbond® interior/exterior with stainless steel floor
- Adjustable digital thermostat for flexible cooling and accuracy
- Time saving and cost effective automatic defrost and vaporisers
- 100% CFC free polyurethane foam for greater insulation and added strength
- Double glazed doors with one-piece door frame
- Removable refrigeration module for easy replacement
- Rated for 43°C ambient working conditions
- Waste heat condensate tray
- Temperature ranges from -18° to +10°C
- Full length vertical fluorescent lighting for enhanced product display on glass door model.



HR2GDCB



H 2040mm
on castors

D 710mm

W 1000mm

HR3GDCB



H 2040mm
on castors

D 710mm

W 1467mm

LR2SDCB



Model	Temp°C	Amp	Shelves (per door)	Net Capacity (Litres)
2 Door External dimensions 1000mm x 710mm x 2040mm				
HR2	+1/+4	3.5	4	750
LR2	-18/-22	4.0	4	750
3 Door External dimensions 1467mm x 710mm x 2040mm				
HR3	+1/+4	4.5	4	1150
LR3	-18/-22	6.5	4	1150

Williams Refrigeration reserve the right to change specifications without notice.

Controls

- Digital microprocessor control with adjustable electronic thermostat and defrost interval to ensure excellent temperature control
- On/off switch for interior light (glass doors standard).

Construction

- Designed and manufactured to international quality standards
- Colorbond® interior and exterior except rear and under
- Stainless steel interior floor
- Self closing double glazed doors with 90° dwell
- Four PC adjustable shelves
- Front locking castors.

Refrigeration

Self Contained:

- Forced air refrigeration system
- 240 volt single phase power
- 43°C ambient operating temperature
- Waste heat condensate tray.

Remote:

- Forced air refrigeration system
- 240 volt single phase power
- Supplied with evaporator, digital thermostat and tx valve and condensate drain exit.

Options

- Stainless steel interior and exterior
- Solid doors (full or half)
- Legs (add 30mm to height)
- Pass through refrigerators (2 door only) Foodservice applications only.
- Custom colours and illuminated sign housing
- Locks
- Double glazed Argon Low E glass
- Heated double glazed doors
- Light in solid door model.



Colorbond®
Durability



Williams Refrigeration Australia Pty Ltd

38-42 Gaine Road Dandenong South Victoria Australia 3175
 Telephone: 03 8787 4747 Facsimile: 03 8787 4787 FreeCall: 1800 338 148
 Email: sales@williamsref.com.au www.williamsref.com.au ABN 25 006 630 084