

extensive range  
leading brands  
design & install

SAFE & SECURE  
ONLINE SHOPPING

australia wide authorised catering equipment distributor

Visit Australia's leading Commercial Catering Equipment website for instant quotes on the major catering equipment brands at very competitive prices.

[www.mvocateringsolutions.com.au](http://www.mvocateringsolutions.com.au)

#### Showroom locations

MVO Services  
3 Toonburra Street  
Bundaberg QLD 4670  
Ph (07) 4152 7277

MVO Services  
5/85 Beach Road  
Hervey Bay QLD 4655  
Ph (07) 4194 0722

Your requested document is included below



## Bottom Mounted Upright Display Refrigerator



### Quartz

#### Benefits

- One and two door models
- Undermount refrigeration unit for optimal product display
- Available in Colorbond® and stainless interior/exterior
- Adjustable digital thermometer for flexible cooling and accuracy
- Time saving and cost effective automatic defrost and vaporisers
- 100% CFC free polyurethane foam for greater insulation and added strength
- Operating temperatures from 1°C to 4°C
- Waste heat condensate tray
- Rated for 43° ambient working conditions
- Double glazed doors with one piece door frame
- Full length vertical fluorescent lighting for enhanced product display.

**HQ14**



H 2040mm on castors

D 710mm

W 650mm

**HQ28**



H 2040mm on castors

D 710mm

W 1000mm

Model	Temp°C	Amp	Shelves	Net Capacity (Litres)
<i>External dimensions 650mm x 710mm x 2040mm</i>				
HQ14	+1/+4	3.5	4	400
<i>External dimensions 1000mm x 710mm x 2040mm</i>				
HQ28	+1/+4	3.5	4	670

*Williams Refrigeration reserve the right to change specifications without notice.*

**Controls**

- Digital microprocessor control with adjustable electronic thermostat and defrost interval to ensure excellent temperature control
- On/off switch for interior light.

**Refrigeration**

- Self contained cabinet
- Forced air refrigeration system
- 240 volt single phase power
- 43°C ambient operating temperature
- Waste heat recovery vaporiser.

**Construction**

- Designed and manufactured to international quality standards
- Colorbond® interior and exterior except for rear and floor
- Stainless steel interior floor
- Self closing double glazed doors with 90° dwell
- Four PC adjustable shelves
- Front locking castors.

**Options**

- Stainless steel interior and exterior
- Legs (add 30mm to height)
- Locking tabs.



Colorbond® Durability

